

OUTBREAK™

POWER OVER ETHERNET SPLITTER



POE splitter for delivering power via
POE to non-POE network devices

Delivers 5V or 12V DC to non-POE devices from a POE network source
by splitting data and power.

Simple POE splitter delivering clean power to non-POE devices

Fully IEEE 802.3af compliant and gigabit compatible

Steps down POE voltage (48V) to 5V or 12V DC

Compact unit with integral wall mount lugs

Ideal for non-POE wireless access points, IP phones, IP cameras



TECHNICAL SPECIFICATION

OUTBREAK™

POWER	Input voltage Input current	36V to 56V DC, receiving power on either data or spare pairs 0.6A at 36V maximum load	
OUTPUT POWER	OUTBREAK 5 OUTBREAK 12 DC Output connector	12.5 watts at 5V DC 12-14 watts at 12V DC Output with short-circuit protection Barrel connector 9mm x 2.5mm x 5.5mm, centre positive	
POE STANDARDS		IEEE 802.3af POE	
ETHERNET INTERFACE		RJ45 Data and POE IN port RJ45 Data OUT port 10/100/1000 Base-T compatible	
LEDS	Status indicator	Green LED ON - Output OK	
PHYSICAL/ENVIRONMENTAL	Dimensions Weight Mounting Operating temperature Relative humidity Compliance	L 100mm (excluding flying lead) W 56mm H 28mm 200g (7.0oz) Integral wall-mount lugs 0°C to +40°C (32°F to 104°F) 5% to 90% non-condensing CE, FCC, RoHS	
PRODUCT CODES	VOR-OB5 VOR-OB12	OUTBREAK 5V OUTBREAK 12V	5V POE Splitter 12V POE Splitter



OUTBREAK 12V



OUTBREAK 5V



veracity

Americas & Asia Sales :

Veracity USA Inc.
 65 Harristown Road
 Glen Rock
 NJ 07452

USA
 Tel: 1-800-679-1590
 Fax: 1-800-679-0714
 www.veracityglobal.com
 sales@veracityusa.com

EMEA Sales :

Veracity UK Ltd
 Prestwick International Aerospace Park
 4 Dow Road
 Prestwick
 KA9 2TU
 UK

Tel +44 (0) 1292 264967
 Fax +44 (0) 845 528 1081
 www.veracityglobal.com
 sales@veracityuk.com