



LRN-410S

4CH 5MP NVR with PoE Switch

Benefits

- Easy plug and play functionality with automatic device discovery and simple setup
- Improved Install wizard for easy configuration
- Easily connect to NVR from anywhere with your smartphone without having to set up a complex network
- Smart search using camera metadata to narrow search results
- USB keyboard supported
- Records high resolution stream and VGA stream at the same time, avoiding playback delays due to narrow band network
- Remote firmware upgrades provided


Key Features

- Up to 4CH 5MP
- H.265, H.264, MJPEG codec
- 30Mbps network camera recording
- Plug & play by 4 PoE ports
- Up to 1 SATA (Max. 6TB)
- HDMI / VGA local monitor
- P2P service (QR code connect)
- Dual Track Recording

LRN-410S	
DISPLAY	
NETWORK CAMERA	
Inputs	Max. 4CH
Resolution	5MP ~ CIF
Protocols	Wisenet, ONVIF
DECODING	
Local Display	HDMI: 1920x1080, 1280x720
Resolution	5MP(30fps), 3MP(60fps), 2MP(120fps), 720p(240fps), D1(240fps)
PERFORMANCE	
RECORD	
Compression	H.265, H.264, MJPEG
Recording Bandwidth	Max. 30Mbps
Resolution	5MP ~ CIF
Mode	Normal, Schedule(Continuous/Event), Event (Pre/Post), Dual track Recording
Event Trigger	Alarm Input, Video Loss, Camera Event(Alarm, MD, Video Analytics, Defocus)
Event Action	e-Mail, PTZ Preset, Buzzer, Monitor Out
SEARCH & PLAY	
Playback Bandwidth	Max. 32Mbps(4CH simultaneously)
User	Max. 4 Users (Local 1, Remote 3)
Simultaneous playback	Max. 4CH(Local Monitor, Network)
Fisheye Dewarping	WEB / CMS / Mobile
STORAGE	
Supported HDD	Up to 6TB
HDD Slot	SATA 1ea(Max. 6TB)
BACKUP	
File backup	BU/Exe(GUI), JPG/AVI(Network)
Function	Multi channel(Upto 4CH) Play, Date-Time/Title display
NETWORK	
Protocol	IPv4, IPv6, TCP/IP, UDP/IP, RTP (UDP), RTP (TCP), RTSP, NTP, HTTP, DHCP (Server, Client), PPPoE, SMTP, ICMP, IGMP, ARP, DNS, DDNS, uPnP, HTTPS, SNMP, ONVIF (Profile-S), SUNAPI(Server, Client)
DDNS	Wisenet DDNS
AUDIO	
Input/Output	4CH(network)
Compression	G.711, G.726, AAC(16/48KHz)
Audio Communication	2-Way
Max Remote Users	Search(3), Live Unicast(10), Multicast(20)
Security	HTTPS(SSL) Login Authentication Digest Login Authentication IP Address Filtering User access log 802.1X Authentication(EAP-TLS, EAP-LEAP) Device Certificate(Hanwha Techwin Root CA)
Viewer Software	SSM, Webviewer, Smart Viewer, Wisenet mobile Support SDK/CGI(SUNAPI) for integration to 3'rd party VMS

Dimensions

Unit:mm(inch)



LRN-410S

FUNCTIONS

CAMERA SETUP

Item	IP address, Add profile edit, Bitrate, Compression, GOP, Quality, Camera MD setup, Wisestream, Dynamic GOV/FPS, VA Setup Camera video setup (Simple focus, Brightness/Contrast, Flip/Mirror, IRIS, WDR, D&N, SSSNR, Shutter, SSSDR, DIS), Fisheye Dewarping Mode, Hallway View Setup, Camera Webpage
------	--

PTZ

Control	Via GUI, Webviewer
---------	--------------------

SMART PHONE

Support Model	iOS, Android
Protocol Support	RTP, RTSP, HTTP, HTTPS, CGI(SUNAPI)
Control	Live(Multi-Profile Support), Playback
Max. Remote Users	Search(3), Live Unicast(10)

REDUNDANCY

ARB	Support
Easy configuration	P2P(QR code)

INTERFACE

HDMI	1EA
Ethernet	RJ-45(10/100BASE-T) x 1 RJ-45(PoE+) x 4
USB	2EA(Front 1, Rear 1)

SYSTEM

System Control	Mouse, IR remocon, Web
Language	English, French, German, Italian, Spanish, Russian, Turkish, Polish, Dutch, Swedish, Czech, Portuguese, Danish, Rumanian, Serbian, Croatian, Hungarian, Greek, Norwegian, Finnish, Korean, Chinese, Japanese, Thai, Vietnamese

ENVIRONMENTAL

Operating Temperature	0°C to +40°C(32°F to 104°F)
Operating Humidity	20% ~ 85% RH

ELECTRICAL

Power Input	54VDC / 1.20A
Power Consumption	Max. 47W(1HDD, PoE on) Max. 7.4W(1HDD, PoE off)
PoE Budget	Max. 35W

MECHANICAL

Colour / Material	Black / Metal
Dimension (WxHxD)	W300.0 x H47.1 x D208.4 mm (11.8" x 1.85" x 8.2") (1U)
Weight	0.99Kg (2.18lb)

* The latest product information / specification can be found at hanwha-security.com

* Design and specifications are subject to change without notice.

* Wisenet is the proprietary brand of Hanwha Techwin.